

## MARTIN WISMAN SPX 250 B-Stock

Šifra: 8140  
Kategorija proizvoda: Pasivne Zvučne Kutije  
Proizvođač: Martin Wisman

Cena: 312,00 KM

### MARTIN WISMAN SPX 250 B-Stock

High

Impact Molded Polypropylene Enclosure  
10L250-82 10 LF Transducer  
1.4"Voice Coil, 1 Exit Titanium  
Compression Driver  
Smooth Response With High Power  
Handling Capcity (Continuous Program/RMS),  
1000W/250W  
5 Integral Suspension Points  
Complete Mounting Solutions

### General Description and Applications:

The SPX 250 features a molded polypropylene enclosure that it inherently weather resistant. MARTIN WISMAN audio used advanced program techniques to create the most successful and influential professional speaker system. High power, efficiency, lower distortion and great low frequency extension provide an unbelievable performance. SPX 250 can be used for live sound reinforcement, vocals, speech and music playback in entertainment, schools, pub, coffee shop and outdoor venues. Portability is one of the important factors for choice especially. For permanent suspension or attaching brackets, the SPX 250 also has two M8 inserts on the top and bottom, two on the side, for a total of 5.

### Technical Specifications

Freq. Range (-10dB):	60Hz~20kHz
Freq. Response (-3dB):	70Hz~20kHz
Rec.Hipass Frequency:	30Hz
Axial Sensitivity:	95dB(1W/1m)
Max Calculated SPL:	125dB
Rated System Power:	250W Continuous 1000W Peak
LF Transducer:	10"/65mm
HF Transducer:	1"34mm
Crossover Frequency:	2.0kHz
Nominal Impedance:	8 Ohms
Connector:	2 x NL4 Speakon
Dim (HxWxD):	557mmx332mmx313mm
Net Weight:	16Kg
Shipping Weight:	18Kg
Horizontal Clearance:	800