

Biamp - Apart MASK 4CT-BL - Nazidni zvučnik

Šifra: 13442
Kategorija proizvoda: Outdoor Zvučnici
Proizvođač: Biamp - Apart



Cena: 272,00 KM

The MASK4CT has a unique design and delivers a crystal clear sound for all music applications. The MASK4CT can be used as a 70V/100V speaker with power tapping on 20 - 10 - 5 - 2.5 watts in 100V or as a low impedance 16 Ohm speaker. This results in a versatile speaker that can be used in any location and any application. The cabinet is made of high quality enforced PP4 ABS, with an aluminium grill. The design of the MASK4CT ensures high quality and long lasting performance in indoor and outdoor use, even under extreme weather conditions. The MASK4CT has a powerful 4.25" coated paper cone woofer and a 1" silk dome tweeter which results in a high SPL and extremely low distortion.

This ensures an unprecedented clarity over the whole frequency spectrum. The built-in Apart 3-step protection and the high-quality components make the MASK4CT an ultra- reliable, fail safe loudspeaker even at high power loads. Thanks to the revolutionary design of the ClickMount bracket, the MASK4CT is without a doubt the fastest and most installer friendly loudspeaker to-date. The pre-defined clicks on the Clickmount ensure a perfect alignment for every loudspeaker. With the discrete cable management system, integrated spirit level and in/out connectors, the full cabling is done on the bracket. To complete the installation simply click the loudspeaker on the ClickMount!

height	238 mm	width	144 mm
depth	144 mm	loudspeaker system	2-way
woofer size	4,25 inch	woofer cone material	coated paper
tweeter size	1 inch	mounting system	clickmount
100V transformer power taps	20 - 10 - 5 - 2.5 watts	70V transformer power taps	20 - 10 - 5 - 2.5 - 1.25 watts
impedance (ohms)	16	low impedance dynamic power	70 watts
low impedance RMS power	50 watts	SPL 1W/1m	89 dB
max SPL 1m	104 dB	frequency response	80 - 20k Hz
main construction material	ABS plastic	grille main material	aluminium
IP rating	64	Horizontal dispersion angle 1000 Hz	180°
Vertical dispersion angle 1000 Hz	180°	closest RAL colour (subject to deviations)	RAL9016 (W) / RAL9011 (BL)