Firma: Player 387 doo
Adresa: Njegoševa 16
Telefon: +387 55 209 104
Fax:
PIB: 403444110009
E-mail: porudzbine@player.ba

# Biamp - Apart MASK4CT-W - Nazidni zvučnik



Šifra: 12599
Kategorija prozivoda: Outdoor Zvučnici
Proizvođač: Biamp - Apart

## Cena: 272,00 KM

Complete with time saving innovative click mount system for quick and simple installation.
The MASK4CT background music loudspeaker benefits from a stylish innovative design and can be used in low impedance 16 ohms (up to 4 loudspeakers in parallel on a standard 4 ohms amplifier channel) or in 100 volt line systems. Power tappings of 20,10, 5 & 2.5 watts are selected via a rotary switch on the back.
The powerful 4.25" woofer and Ferro-fluid cooled 1" silk dome tweeter offers high SPL and ultra low distortion. The internal bracketing and shape of the cabinet avoids internal interference and optimises the sound quality.
Built in auto-reset overload protection - 3-step Protection Guard is effective even at high power loads!
Suitable for use either indoors or outdoors, supplied with wall mounting bracket and available in black or white.

Timeless design
Weather resistant (aluminium grille)
ClickMount: click & connect
Connectors with passthrough and 0.14 – 4 mm² solid or stranded wire capacity
Wall and ceiling mountable
Integrated spirit level
Unique 3 stage overload protection
Asymmetric tweeter horn design
Coated 4.25”LF driver for MASK4C(T)
Horn loaded silk dome tweeter
Paintable in any RAL color
Rotatable logo
70W power handling for MASK4C(T)
70V and 100V compatible
Integrated safety nut for SAFCAB (supplied)
The installer can mount the ClickMount and connect the speaker cables while the speakers are still safely packed inside the packing carton.
Glass fibre reinforced bracket included
Speakers designed to be used in combination with the included
ClickMount
Incorporated 5º downward listening angle

| | |
|---|---|
| **height** | 238 mm |

| | |
|---|---|
| **width** | 144 mm |
| **depth** | 144 mm |
| **loudspeaker system** | 2-way |
| **woofer size** | 4,25 inch |
| **woofer cone material** | coated paper |
| **tweeter size** | 1 inch |
| **mounting system** | clickmount |
| **100V transformer power taps** | 20 - 10 - 5 - 2.5 watts |
| **70V transformer power taps** | 20 - 10 - 5 - 2.5 - 1.25 watts |
| **impedance (ohms)** | 16 |
| **low impedance dynamic power** | 70 watts |
| **ow impedance RMS power** | 50 watts |
| **SPL 1W/1m** | 89 dB |
| **max SPL 1m** | 104 dB |
| **frequency response** | 80 - 20k Hz |
| **main construction material** | ABS plastic |
| **grille main material** | aluminium |
| **IP rating** | 64 |
| **Horizontal dispersion angle 1000 Hz** | 180° |
| **Vertical dispersion angle 1000 Hz** | 180° |
| **Net weight product (kg)** | 1.85 |

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.