

## Biamp - Apart MASK4CT-W - Nazidni zvučnik

Šifra: 12599  
Kategorija proizvoda: Outdoor Zvučnici  
Proizvođač: Biamp - Apart



**Cena: 272,00 KM**

Complete with time saving innovative click mount system for quick and simple installation. The MASK4CT background music loudspeaker benefits from a stylish innovative design and can be used in low impedance 16 ohms (up to 4 loudspeakers in parallel on a standard 4 ohms amplifier channel) or in 100 volt line systems. Power tapings of 20,10, 5 & 2.5 watts are selected via a rotary switch on the back.

The powerful 4.25" woofer and Ferro-fluid cooled 1" silk dome tweeter offers high SPL and ultra low distortion. The internal bracketing and shape of the cabinet avoids internal interference and optimises the sound quality.

Built in auto-reset overload protection - 3-step Protection Guard is effective even at high power loads! Suitable for use either indoors or outdoors, supplied with wall mounting bracket and available in black or white.

Timeless design

Weather resistant (aluminium grille)

ClickMount: click & connect

Connectors with passthrough and 0.14 - 4 mm<sup>2</sup> solid or stranded wire capacity

Wall and ceiling mountable

Integrated spirit level

Unique 3 stage overload protection

Asymmetric tweeter horn design

Coated 4.25" LF driver for MASK4C(T)

Horn loaded silk dome tweeter

Paintable in any RAL color

Rotatable logo

70W power handling for MASK4C(T)

70V and 100V compatible

Integrated safety nut for SAF-CAB (supplied)

The installer can mount the ClickMount and connect the speaker cables while the speakers are still safely packed inside the packing carton.

Glass fibre reinforced bracket included

Speakers designed to be used in combination with the included ClickMount

Incorporated 5° downward listening angle

|               |        |
|---------------|--------|
| <b>height</b> | 238 mm |
|---------------|--------|

|  |                                |
|--|--------------------------------|
| <b>width</b>                               | 144 mm                         |
| <b>depth</b>                               | 144 mm                         |
| <b>loudspeaker system</b>                  | 2-way                          |
| <b>woofer size</b>                         | 4,25 inch                      |
| <b>woofer cone material</b>                | coated paper                   |
| <b>tweeter size</b>                        | 1 inch                         |
| <b>mounting system</b>                     | clickmount                     |
| <b>100V transformer power taps</b>         | 20 - 10 - 5 - 2.5 watts        |
| <b>70V transformer power taps</b>          | 20 - 10 - 5 - 2.5 - 1.25 watts |
| <b>impedance (ohms)</b>                    | 16                             |
| <b>low impedance dynamic power</b>         | 70 watts                       |
| <b>ow impedance RMS power</b>              | 50 watts                       |
| <b>SPL 1W/1m</b>                           | 89 dB                          |
| <b>max SPL 1m</b>                          | 104 dB                         |
| <b>frequency response</b>                  | 80 - 20k Hz                    |
| <b>main construction material</b>          | ABS plastic                    |
| <b>grille main material</b>                | aluminium                      |
| <b>IP rating</b>                           | 64                             |
| <b>Horizontal dispersion angle 1000 Hz</b> | 180°                           |
| <b>Vertical dispersion angle 1000 Hz</b>   | 180°                           |
| <b>Net weight product (kg)</b>             | 1.85                           |