

## Scale Nordic SGM-TRM-0150

Šifra: 15212  
Kategorija proizvoda: Linijski Kablovi  
Proizvođač: Scale Technologies

**Cena: 26,00 KM**

High performance microphone cable  
Unique, high quality, woven outer covering (6,5mm)  
Hand soldered Custom male XLR connector  
Hand soldered Custom 1/4-inch TRS connector with 24K gold-plated contacts  
Conductor: 28 x 0.10 x 2mm (OFC)  
PVC Jacket: 6 mm  
Spiral shield: 84 x 0.10 (OFC)  
4-core twining process: 4-core twining process (2 conductors +2 filled PVC tubes)  
Included 2 cable straps  
Lifetime guarantee  
Available in 1.5 meter, 3 meter and 5 meter lengths

### Specifications:

#### Cable:

Type: Custom Tweed  
Microphone Cable  
Color: black with blue  
pattern  
Overall diameter: 6.5  
mm +/- 0.1 mm  
Conductor area: 0.22  
mm<sup>2</sup> / AWG 24  
Composition of  
conductor: 28 x 0.10  
mm, bare annealed  
copper, OFC  
Conductor insulation: LD-  
PE Ø 1.35 mm  
Composition of cores: 4-  
core twining process, 60  
MM one turn, left hand  
Composition of  
conductor: 28 x 0,10 mm  
Filler: Cotton Strand

#### Scale Nordic SGM-TRM-0150

**4-  
core**

#### twining process

4-core twining process (2 conductors +2 filled PVC tubes). The advantage of this is that the physical structure of a four-core process are more stable and produces less noise when the cable is moving compared to a two-core cable

#### Features:

Shield: 84 \*0.10 mm,  
bare annealed copper,  
OFC

Jacket material:  
Phthalate free PVC with  
restricted substance

Working temperature:  
Mobile: -5°C to +70°C,  
Fixed: -20° to +70°C

#### **Connectors:**

Model name: SC013 /  
SC002

Product type: XLR male /  
TRS male

Number of poles: 3

Contact surface: black

Connection type: solder  
contact

Colour: gold

Housing: Cast zinc

Clamping sleeve:  
Polyacetal (POM)

Temperature range: -30  
°C to +80 °C