Firma: Player 387 doo
Adresa: Njegoševa 16
Telefon: +387 55 209 104
Fax:
PIB: 403444110009
E-mail: porudzbine@player.ba

Scale Nordic TGM-TRM-0250

Šifra: 15211
Kategorija prozivoda: Linijski Kablovi
Proizvođač: Scale Technologies

Cena: 28,00 KM



4-core twining process
4-core twining process (2 conductors +2 filled PVC tubes). The advantage of this is that the physical structure of the four-core is more stable and produces less noise when the cable is moving compared to the two-core cable

Features:

High performance michrophone cable

6,5mm high quality rubber cable

Hand soldered Custom male XLR connector

Hand soldered Custom 1/4-inch TRS connector with 24K gold-plated contact

Conductor: 28 x 0.10 x 2mm (OFC)

PVC Jacket: 6.5mm

Spiral shield: 84 x 0.10 (OFC)

4-core twining process: 4-core twining process (2 conductors +2 filled PVC tubes)

Included 2 cable straps

Lifetime guarantee

Available in 2.5 meter and 5 meter lengths

Specifications:

Cable:

Type: MC04

Color: black

Conductor area: 0.22 mm2 / AWG 24

Composition of conductor: 28 x 0.10 mm, bare annealed copper, OFC

Conductor insulation: LD-PE Ø 1.35 mm

Composition of cores: 4-core twining process, 60 MM one turn, left hand

Composition of conductor: 28 x 0,10 mm

Filler: Cotton Strand

Shield: 84 *0.10 mm, bare annealed copper, OFC

Jacket material: Phthalate free PVC with restricted substance

Working temperature: Mobile: -5°C to +70°C, Fixed: -20° to +70°C

Connectors:

Model name: SC013 / SC002

Product type: XLR male / TRS male

Number of poles: 3

Contact surface: black

Connection type: solder contact

Colour: gold

Housing: Cast zinc

Clamping sleeve: Polyacetal (POM)

Temperature range: -30 °C to +80 °C

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.