

## Scale Nordic TGM-TRM-0250

Šifra: 15211  
Kategorija proizvoda: Linijski Kablovi  
Proizvođač: Scale Technologies

**Cena: 28,00 KM**

High performance microphone cable  
6,5mm high quality rubber cable  
Hand soldered Custom male XLR connector  
Hand soldered Custom 1/4-inch TRS connector with 24K gold-plated contact  
Conductor: 28 x 0.10 x 2mm (OFC)  
PVC Jacket: 6.5mm  
Spiral shield: 84 x 0.10 (OFC)  
4-core twining process: 4-core twining process (2 conductors +2 filled PVC tubes)  
Included 2 cable straps  
Lifetime guarantee  
Available in 2.5 meter and 5 meter lengths

### Specifications:

#### Cable:

Type: MC04  
Color: black  
Conductor area: 0.22 mm<sup>2</sup> / AWG 24  
Composition of conductor: 28 x 0.10 mm, bare annealed copper, OFC  
Conductor insulation: LD-PE Ø 1.35 mm  
Composition of cores: 4-core twining process, 60 MM one turn, left hand  
Composition of conductor: 28 x 0,10 mm  
Filler: Cotton Strand  
Shield: 84 \*0.10 mm, bare annealed copper, OFC  
Jacket material: Phthalate free PVC with

#### Scale Nordic TGM-TRM-0250

**4-core**

#### twining process

4-core twining process (2 conductors +2 filled PVC tubes). The advantage of this is that the physical structure of the four-core is more stable and produces less noise when the cable is moving compared to the two-core cable

#### Features:

restricted substance

Working temperature:

Mobile: -5°C to +70°C,

Fixed: -20° to +70°C

### **Connectors:**

Model name: SC013 /  
SC002

Product type: XLR male /  
TRS male

Number of poles: 3

Contact surface: black

Connection type: solder  
contact

Colour: gold

Housing: Cast zinc

Clamping sleeve:

Polyacetal (POM)

Temperature range: -30  
°C to +80 °C