©©© not found or type unknown

Firma: Player 387 doo Adresa: Njegoševa 16 Telefon: +387 55 209 104

Fax:

PIB: 403444110009

E-mail: porudzbine@player.ba

WHARFEDALE Linton Walnut (par) zvučnici sa stalcima

Šifra:

Kategorija prozivoda: Hi-Fi Paketi

Proizvođač: Wharfedale

Cena: 1.800,00 KM

WHARFEDALE-Linton Walnut (par) zvučnici sa stalcima

Wharfedale Linton speakers are among the most iconic models in Wharfedale's long history of loudspeakers. Like the recent release of Denton 85, this latest Linton model follows in the trend for updated versions of classic designs. Retaining the classic sound of the original with updated drivers, crossovers and reworked cabinets, these are beautiful speakers and an enticing alternative to more modern options.

Linton Legacy

Linton embodies the brand's pioneering research through the 60s, 70s and 80s. With a heritage dating back to 1965, Linton was manufactured in accordance with the principles of quality and value for money.

Large Driver

Linton exploits its wide baffle by employing a bass driver with a 200mm Kevlar cone that is larger than most modern drivers mounted on a sturdy die-cast chassis. A 135mm midrange driver sits above this and supports a woven kevlar cone housed within its own internal enclosure. To finish, a 25mm fabric-dome tweeter is employed featuring high-flux ferrite magnet to handle high frequencies.

Craftsmanship

The new version of Wharfedale Linton reinforces these principles balancing high craftsmanship, lifelike sound quality and affordability within an elegantly shaped speaker whose various incarnations have sold in millions across the globe.

Original Sound

The new Linton preserves the rich, warm and realistic sound that the original Linton was renowned for while infusing it with space and detail that entices you to explore your entire music collection again.

Bass reflex

Transducer Complement

3-way

Bass Driver

8"(200mm) black woven Kevlar® cone

Midrange Driver

5"(135mm) black woven Kevlar® cone

Treble Driver

1" (25mm) soft dome

Sensitivity (2.0V @ 1m)
90dB
Recommended Amplifier Power
25-200W
Peak SPL
110dB
Nominal Impedance
6Ω
Minimum Impedance
3.5Ω
Frequency Response(+/-3dB)
40Hz ~ 20kHz
Bass Extension(-6dB)
35Hz
Crossover Frequency
630Hz & 2.4kHz
Height (on plinth)
565mm
Width
300mm
Depth (with terminals)
(330+30)mm
Net Weight 18.4kg
18.4kg/pcs

AV Shield

No