

FOCUSRITE Clarett+ 2Pre

FOCUSRITE Clarett+ 2Pre

Šifra: 16011 Form Factor	Tabletop
Kategorija proizvoda: USB Zvučne kartice Proizvođač: Focusrite Display	None
Cena: 700,00 KM	Analog: 2 Inputs / 4 Outputs Digital: 8 Inputs / 0 Outputs
Channels of I/O	
Max Sample Rate/Resolution	192 kHz / 24-Bit
Number of Mic Preamps	2
Input Level Adjustment	2 x Knob
Expansion Slots	None
Pad	None
Gain/Trim Range	Mic/Line/Hi-Z Inputs: +57 dB
High-Pass Filter	None
Solo/Mute	None

Connectivity

Analog Audio I/O	2 x Combo XLR-1/4" TRS Balanced/Unbalanced Mic/Line/Hi-Z Input (Front Panel) 4 x 1/4" TRS Balanced Line/Monitor Output 1 x 1/4" TRS Unbalanced Headphone Output (Front Panel)
Phantom Power	48 V, Selectable On/Off (Selectable on Individual Inputs)

Digital Audio I/O	1 x TOSLINK Optical ADAT Input (S/MUX Support)
Host Connection / USB	1 x USB Type-C (USB 2.0)
USB (Non-Host)	<i>None</i>
Sync I/O	<i>None</i>
Network I/O	<i>None</i>
MIDI I/O	1 x DIN 5-Pin Input 1 x DIN 5-Pin Output
Wireless Connectivity	<i>None</i>

Performance

Frequency Response	Mic Inputs: 20 Hz to 20 kHz ± 0.03 dB 20 Hz to 35 kHz ± 0.15 dB Line Inputs: 20 Hz to 20 kHz ± 0.05 dB 20 Hz to 35 kHz ± 0.15 dB Hi-Z Inputs: 20 Hz to 20 kHz ± 0.04 dB 20 Hz to 35 kHz ± 0.15 dB Line, Monitor Outputs: 20 Hz to 20 kHz ± 0.02 dB 20 Hz to 35 kHz ± 0.02 dB Headphone Outputs: 20 Hz to 20 kHz ± 0.06 dB 20 Hz to 35 kHz ± 0.07 dB
Max Input Level	Mic Inputs: +18 dBu Line Inputs: +26 dBu Hi-Z Inputs: +15 dBu
Max Output Level	Line/Monitor Outputs: +18 dBu Headphone Outputs: +16 dBu
Impedance	Inputs: 2.2 Kilohms

Dynamic Range	Mic Inputs: 118 dB (Min Gain) Line Inputs: 118 dB (Min Gain) Hi-Z Inputs: 116 dB Line/Monitor Outputs: 124 dB Headphone Outputs: > 118 dB
---------------	---

THD+N	Mic Inputs: -110 dB (+20 dB Input, at -1 dBFS) Line Inputs: -100 dB (Min Gain, at -1 dBFS) Hi-Z Inputs: -96.5 dB (Min Gain, at -1 dBFS) Line/Monitor Outputs: -106 dB Headphone Outputs: -104 dB
-------	--

EIN	Mic Inputs: < -129 dBu
-----	----------------------------------

Digital Audio

Sample Rates	44.1 / 48 / 88.2 / 96 / 176.4 / 192 kHz
Sample Rate Conversion	<i>None</i>
Bit Depths	24-Bit (AD/DA Conversion)
Sync Sources	ADAT, Internal, S/PDIF
Memory Card Slot	<i>None</i>

Compatibility

OS Compatibility	macOS 10.11 or Later macOS 11 Windows 7 or Later
------------------	--

Included Software	None
Compatible Software (Not Included)	Any Core Audio (Mac) Compliant Software
Included Plug-Ins	Preamp & Channel Strip: Brainworx bx_console Focusrite SC Dynamics: Focusrite Red 3 Compressor Equalization: Focusrite Red 2 Equalizer
Supported Drivers/API & Plug-Ins	Proprietary
Mobile Device Compatibility	None
Required Hardware	Available USB 2.0 Port, USB 3.0 / 3.1 Gen 1 Port, or USB Type-C Port USB Cable (Included)
Internet Connection	Required for Registration, Software/Driver Download

Power

Power Requirements	AC/DC Power Adapter (Included) or USB Bus Power
AC/DC Power Adapter	12 VDC at 1.5 A, Center-Positive (Included)

Physical

Anti-Theft Features	Kensington Security Slot
Dimensions	8.27 x 6.34 x 2.17" / 21.01 x 16.1 x 5.51 cm
Weight	3.0 lb / 1.4 kg

Packaging Info

Package Weight	4.085 lb
Box Dimensions (LxWxH)	10.6 x 10.2 x 4.5"