

Marantz CD60 Black CD Plejer

Šifra: 16461

Kategorija proizvoda: CD Plejeri

Proizvođač: Marantz



Cena: 1.566,00 KM

Glatki transport diska ovog plejera ima lepu, stabilnu asistenciju u robusnoj čeličnoj konstrukciji sa duplim dnom, i aluminijumskom prednjom pločom na prednjem panelu. Sa više od 7 kilograma, ima zadovoljavajuću težinu, garant dodatne stabilnosti.

DAC opcije & pojačalo za slušalice

CD60 poseduje digitalni audio konverter referentne klase, sa rezolucijom do 24-bit/192kHz. Bilo da koristite CD čitač ili koristite USB port na prednjem panelu, za čitanje sa eksternog fleš drajva - digitalni filter pružiće vam mogućnost da reprodukciju prilagodite sopstvenom slušalačkom iskustvu. Takođe možete upotrebiti i optički ili koaksijalni digitalni izlaz, za povezivanje sa spoljnim DAC-om.

Ugrađeno HDAM®-SA2 pojačalo za slušalice poseduje tri Gain podešavanja za savršeno uklapanje sa praktično bilo kojim slušalicama.

Product highlights:

plays CDs, CD-Rs & CD-RWs plus WMA and MP3 CDs

supports FLAC, WAV, AIFF, ALAC and DSD playback from a connected USB flash drive (sold separately)

high-performance 24-bit/192kHz digital-to-analog converter
DSD 5.6MHz

selectable digital filter lets you tailor the DAC's performance to your listening preference

double-layered metal bottom plate for vibration resistance

newly optimized Marantz HDAM® (Hyper Dynamic Amplifier Module) used in analog circuitry for faster signal transfer and better transient response

high-performance HDAM-SA2 headphone amplifier with selectable low/mid/high gain settings

robust, high-speed power supply for rich, dynamic sound

frequency response: 2-20,000 Hz

signal-to-noise ratio: 118 dB

total harmonic distortion: 0.0015%

Connections:

optical and coaxial digital outputs

gold-plated stereo analog RCA output

front-panel USB input (Type A) for USB flash drives

built-in headphone amplifier with full-size (1/4") front-panel

headphone jack and volume control

IR flasher input

remote control input/output (for use with compatible Marantz receivers and amps)

General

Unit (W x H x D mm)	442 x 1396
Net weight	7.5kg
Packaging Dimensions (W x H x D mm)	525x2
Panel Color	Available Colors: Silver/Chrome and Matte Black
Front (Center) Panel	Aluminum

Specifications

Frequency response

USB
DSD:
2Hz -
50kHz
3dB)
USB
PCM:
2Hz -
50kHz
1.5dB)
CD: 2H
- 20kHz

Total Harmonic Distortion

USB
DSD:
0.0006
USB
PCM
24bit:
0.0005
CD:
0.0015

Signal to Noise Ratio

USB
DSD:
110dB
USB
PCM
24bit:
118dB
CD:
118dB

Dynamic Range

USB
DSD:
110dB
USB
PCM
24bit:
118dB
CD:
101dB

Line Output Level

2.2Vrms

Headphone Output Level

28mW
32 ohm

Power Consumption

38W

at Standby

0.3W

Audio Feature

HDAM	New HDAM HDAM- SA2
Power Transformer	EI
Headphone Amp	High sl rate op amp + HDA SA2
H/P Amp Gain Setting	Yes (Lo Mid / High)
Digital Filter	Filter 1 Selecta

Connectivity / Playback Capability

CD Compatibility	CD / CD- R/RW / WMA / MP3 / AAC
Data Disc Compatibility	DSD / WAV / ALAC
Fixed Analog Output (RCA)	1 (Gold Plated)
Optical input / output (Maximum Support)	0 / 1
Coaxial input / output (Maximum Support)	0 / 1

Headphone Output

1

Remote Control Bus Terminal

Yes
(RC-5 I
/ Out)
w/
Externa
/
Intern
Select
Switch

Flasher Input

Yes (U
ver)

USB A

1
(Front)
Mass
Storage
Class
5V/1A

Support format

FAT
16/32

USB-A: FLAC / WAV / AIFF / ALAC / DSD

Yes /
Yes /
Yes /
Yes

DSD Native Playback

Yes

USB Firmware Update

Yes

Easy to use