Firma: Player 387 doo
Adresa: Njegoševa 16
Telefon: +387 55 209 104
Fax:
PIB: 403444110009
E-mail: porudzbine@player.ba

MACKIE Thump215XT - Aktivni zvučnik



Šifra: 16859
Kategorija prozivoda: Aktivne Zvučne Kutije
Proizvođač: MACKIE

Cena: 919,00 KM

Mikser **Thump215XT**-a ima dva XLR 1/4"-na Mic/Line kanala sa pripadajućim Gain kontrolama, dok XLR izlaz omogućava povezivanje dodatnih zvučnika u lanac. 3.5-milimetarski TRS Aux ulaz raspoloživ je na drugom kanalu, za povezivanje vašeg omiljenog prenosivog plejera. Čvrsta šasija otporna na bilo kakve spoljašnje uticaje garantuje da će uređaj biti sačuvan od potencijalnih oštećenja pri transportu. Na donjem delu prisutni su i žljebovi za montiranje. Tu je i mogućnost upotrebe **215XT**-a kao podnog monitora, za koncertni/izvođački monitoring na bini.

At a Glance
1400W ultraefficient Class-D amplifier
Built-Like-A-Tank to conquer every gig while lightweight for easy loading
Frequency response: 40 Hz to 20 kHz
Max SPL: 129 dB
15” high-performance woofer
1” compression driver
Outdoor mode optimizes voicing for open air venues
Built-in Feedback Eliminator reduces squeals and out of control rumble
Music Ducking mode automatically reduces the level of Ch.2 when Ch.1 receives signal
Front LED On/Off switch
Standard pole mount
M10 flypoints for permanent install
Monitor wedge provides optimal angle for use as a floor monitor
Universal power supply

Application-Specific Voicing Modes
Under the hood of ThumpXT is some powerful processing that you can tap into to up your sound quality game. With 4 different application-specific voicing modes, you can instantly optimize your speakers for how you use them at the push of a single button.
Music: Made to enhance pre-recorded music

Live: Great for general sound reinforcement
Club: Provides a low-end punch
Monitor: Optimizes the speaker for use as a floor wedge keeping feedback in check

Indoor / Outdoor
Ever bring your speakers from inside a room to the scary outdoors and wonder why it sounds so different? You're not alone, and lucky for you we've thought of everything. When you set up your system out in the wild, just push the Outdoor Mode button and your lovely, full sound is restored.

Bluetooth Connectivity
Easily stream music directly to the speaker and enjoy the wireless freedom to dance around while playing DJ. And while you’re at it, you can dive into the Thump Connect 2 App and adjust anything from system EQ and Voicing Modes to channel levels and venue-specific presets.
Bluetooth connectivity for streaming, speaker linking, and control
Download the Thump Connect 2 app for complete wireless control
Link 2 ThumpXT loudspeakers for a powerful, wireless, music playback system in both stereo and dual-zone configuration

Music Ducking
You've got music playing nice and loud, but it's time for another announcement. Sure, you could mess with your levels every time, but who's got time for that. Simply press the Music Ducking button, and channel 2 will automatically turn down whenever you speak into the mic on channel 1.

Feedback Eliminator
Ever get a little too up close and personal with the microphone only to hear a loud, ear-destroying squeal? That's commonly known as feedback. And it's an unfortunate issue that physics won't change its mind on. But wait! Hit the Feedback Eliminator button and laugh in the face of those silly acoustic laws.

Mackie Thump215XT Specs
Configuration: Active 2-Way

Enclosure Type: Bass-Reflex Loudspeaker
Total Power Capacity: 1400 W Peak
Amplifier Class: Class-D
Drivers
HF Driver 1 x 1" / 25.4 mm Titanium Dome Compression Driver
MF Driver None
LF Driver 1 x 15" / 381 mm Woofer
Performance
Frequency Response: 40 Hz to 20 kHz -10 dB
Maximum SPL: 129 dB SPL
Connectivity
Audio I/O: 2 x Combo XLR-1/4" TRS Balanced/Unbalanced Mic/Line Input
1 x 1/8" / 3.5 mm TRS Female Unbalanced Line Input
1 x XLR 3-Pin Male Balanced Line Output
Network I/O: None
USB: None
Wireless Connectivity: Bluetooth
Signal Processing
EQ: None
Parametric EQ: None
Semi-Parametric EQ: None
Filters: None
Alignment Delay: None
Phase Adjustment: None
Digital Signal Processing: Venue Settings, Voicing Modes
Power
AC Input Power: Universal -
100 to 240 VAC, 50 / 60 Hz
AC Power Connector: 1 x IEC
Power Consumption: 75 W
Physical
Mounting: 1 x Pole Socket (Bottom)
M10 Fly Point
Handles: 1 x Each Side
1 x Top
Dimensions: 685.8 x 442 x 355.6 mm
Weight: 15.9 kg

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.