

MACKIE Thump115S - Aktivni vufer

Šifra: 16860

Kategorija proizvoda: Aktivni Subwooferi

Proizvođač: MACKIE

Cena: 1.410,00 KM



Thump115S ima dva XLR Line ulaza, dva "high-pass" XLR izlaza, i dva "full-range" XLR izlaza. Tu je i varijabilna crossover kontrola, polarni inverter, LED na prednjem panelu, kao i mono/stereo sumiranje za single- ili dual- subvufer upotrebu. Dva "cut-through" rukohvata nalaze se na gornjoj strani, za lako podizanje i prenošenje.

A True Workhorse for Gigging Professionals

1400W Class-D amplifier is designed for ultrareliable, consistent performance

15" high-performance woofer

Built-Like-A-Tank to conquer every gig while lightweight for easy loading

Frequency response: 36 to 200 Hz

Max SPL: 131 dB

Voicing Modes

Flat: Natural balance between deep bass and overall output

Deep: Emphasizes ultra-low frequencies. Great for dance, rap, and electronic music

Punch: Prioritizes highest possible output level. Great for bands and rock music

Variable

Optimized for Your System

Variable crossover frequency

Polarity invert switch

Defeatable front LED

Stereo or mono summing for single- or dual-subwoofer deployment

Variable level control (-6 to +6 dBu)

Front LED On/Off

Versatile Inputs and Outputs

Stereo XLR inputs

Stereo full-range XLR outputs

Stereo high-pass XLR outputs

Versatile Configuration Options

Integrated M20-threaded pole mount

Mackie Thump115S Specs

Configuration: Active Subwoofer

Enclosure: Type Bass-Reflex Subwoofer

Total Power Capacity: 1400 W Peak

Amplifier Class: Class-D

Drivers:

MF Driver None

LF Driver 1 x 15" / 381 mm Woofer

Performance

Frequency Response: 36 Hz to 200 Hz

Maximum SPL: 131 dB SPL

Connectivity

Audio I/O: 2 x XLR 3-Pin Female Balanced Line Input

4 x XLR 3-Pin Male Balanced Line Output

Network I/O: None

USB: None

Wireless Connectivity: None

Signal Processing

Crossover High-Pass: 80 to 160 Hz

EQ: None

Parametric EQ: None

Semi-Parametric EQ: None

Filters: None

Alignment Delay: None

Phase Adjustment -180 / 0°

Digital Signal Processing: Voicing Modes

Power

AC Input Power

Universal: 100 to 240 VAC, 50 / 60 Hz

AC Power Connector: 1 x IEC

Power Consumption: 75 W

Physical

Mounting: 1 x M20 Pole Socket (Top)

Handles: 1 x Each Side

Dimensions: 584.2 x 457.2 x 457.2 mm

Weight: 34 kg