Firma: Player 387 doo
Adresa: Njegoševa 16
Telefon: +387 55 209 104
Fax:
PIB: 403444110009
E-mail: porudzbine@player.ba

# MACKIE Thump115S - Aktivni vufer



Šifra: 16860
Kategorija prozivoda: Aktivni Subwooferi
Proizvođač: MACKIE

## Cena: 1.213,00 KM

**Thump115S** ima dva XLR Line ulaza, dva "high-pass" XLR izlaza, i dva "full-range" XLR izlaza. Tu je i varijabilna crossover kontrola, polarni inverter, LED na prednjem panelu, kao i mono/stereo sumiranje za single- ili dual- sabvufer upotrebu. Dva "cut-through" rukohvata nalaze se na gornjoj strani, za lako podizanje i prenošenje.

**A True Workhorse for Gigging Professionals**
1400W Class-D amplifier is designed for ultrareliable, consistent performance
15” high-performance woofer
Built-Like-A-Tank to conquer every gig while lightweight for easy loading
Frequency response: 36 to 200 Hz
Max SPL: 131 dB

**Voicing Modes**
Flat: Natural balance between deep bass and overall output
Deep: Emphasizes ultra-low frequencies. Great for dance, rap, and electronic music
Punch: Prioritizes highest possible output level. Great for bands and rock music
Variable

**Optimized for Your System**
Variable crossover frequency
Polarity invert switch
Defeatable front LED
Stereo or mono summing for single- or dual-subwoofer deployment
Variable level control (-6 to +6 dBu)
Front LED On/Off

**Versatile Inputs and Outputs**
Stereo XLR inputs
Stereo full-range XLR outputs
Stereo high-pass XLR outputs

**Versatile Configuration Options**
Integrated M20-threaded pole mount

**Mackie Thump115S Specs**
Configuration: Active Subwoofer
Enclosure: Type Bass-Reflex Subwoofer
Total Power Capacity: 1400 W Peak
Amplifier Class: Class-D
Drivers:
MF Driver None
LF Driver 1 x 15" / 381 mm Woofer
Performance
Frequency Response: 36 Hz to 200 Hz
Maximum SPL: 131 dB SPL
Connectivity
Audio I/O: 2 x XLR 3-Pin Female Balanced Line Input
4 x XLR 3-Pin Male Balanced Line Output
Network I/O: None
USB: None
Wireless Connectivity: None
Signal Processing
Crossover High-Pass: 80 to 160 Hz
EQ: None
Parametric EQ: None
Semi-Parametric EQ: None
Filters: None
Alignment Delay: None
Phase Adjustment -180 / 0°
Digital Signal Processing: Voicing Modes
Power
AC Input Power

Universal: 100 to 240 VAC, 50 / 60 Hz
AC Power Connector: 1 x IEC
Power Consumption: 75 W
Physical
Mounting: 1 x M20 Pole Socket (Top)
Handles: 1 x Each Side
Dimensions: 584.2 x 457.2 x 457.2 mm
Weight: 34 kg

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.