Firma: Player 387 doo
Adresa: Njegoševa 16
Telefon: +387 55 209 104
Fax:
PIB: 403444110009
E-mail: porudzbine@player.ba

Neutrik NC3MD-LX



Šifra: 17089
Kategorija prozivoda: Konektori
Proizvođač: Neutrik

Cena: 10,00 KM

Features & Benefits
All metal housing offers best overall RF protection and electromagnetic shieldingDuplex ground contact for excellent contact integrity between chassis and cable connectorMale connector's retention bar replaces plastic design with all metal version improving pull-out forceLarger solder contacts for easier terminationOptional connection to easily join pin1 to chassis groundD-style housing provides installation compatibility with industry standard D mounting dimensions

Technical Information
Product
Title NC3MD-LX
Connection Type XLR
Gender male
Electrical
Capacitance between contacts ≤ 4 pF
Contact resistance ≤ 5 mΩ
Dielectric strength 1,5 kVdc
Insulation resistance > 10 GΩ (initial)
Rated current per contact 16 A
Rated voltage < 50 V
Mechanical
Insertion force ≤ 20 N
Withdrawal force ≤ 20 N
Lifetime > 1000 mating cycles
Wiresize max. 2.5 mm²
Wiresize max. 14 AWG
Wiring Solder contacts
Locking device Latch lock
Chassis shape D
Material
Contact plating 2 µm Ag over 2 µm Ni
Contacts Brass (CuZn35Pb2)
Insert Polyamide (PA66)
Locking element Steel Ck67
Shell Zinc diecast (ZnAl4Cu1)
Shell plating Nickel
Environmental
Flammability UL 94 V-0
Standard compliance IEC 61076-2-103
Protection class IP 40

Solderability Complies with IEC 68-2-20
Temperature range -30 °C to +80 °C

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.