

Neutrik NL4MMX

Šifra: 2320
Kategorija proizvoda: Konektori
Proizvođač: Neutrik

Cena: 15,00 KM



Neutrik // NL4MMX -Speakon Cable To Cable Adapter 4-Pole

4 pole lockable coupler, links two NL2/4F*s together for cable extension. Can be permanently attached to NL2/4F*.

image not found or type unknown



image not found or type unknown



Product	
Gender	male
Electrical	
Contact resistance	≤ 3 mΩ (after lifetime)
Dielectric strength	4 kVdc (peak)
Insulation resistance	> 1 GΩ (after dampheat)
Rated current per contact	15 A rms continuous
Rated current per contact	30 A audiosignal, duty cycle 50 %
Rated voltage	250 V (Insulation)
Attention	speakON is NOT to be used as an AC mains connector!
Mechanical	
Lifetime	> 5000 mating cycles
Locking device	Quick Lock
Material	
Contact plating	4 µm Ag
Contacts	Bronze (CuSn6)
Insert	Polyamide (PA 6 30 % GR)
Shell	Polyamide (PA 6 30 % GR)
Environmental	
Flammability	UL 94 HB
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C

